

SAFETY DATA SHEET**SOLV1540 SCREEN SOLV/LACQ. THINNER**

Version Number 1.1
Revision Date 07/02/2021

Page 1 of 20
Print Date 07/03/2021

SAFETY DATA SHEET**SOLV1540 SCREEN SOLV/LACQ. THINNER****Section 1. Identification**

GHS product identifier : SOLV1540 SCREEN SOLV/LACQ. THINNER
Chemical name : Mixture
CAS number : Mixture
Other means of identification : FO00016684
Product type : liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **AVIENT CORPORATION**
 33587 Walker Road, Avon Lake, OH 44012
 1 (440) 930-1000 or 1 (844) 4AVIENT

Emergency telephone number (with hours of operation) : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 4
 ACUTE TOXICITY (inhalation) - Category 3
 SKIN IRRITATION - Category 2
 EYE IRRITATION - Category 2A

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 70 %

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 10 %

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 2 of 20
 Print Date 07/03/2021

GHS label elements

- Hazard pictograms** : 
- Signal word** : Danger
- Hazard statements** : Harmful if swallowed.
 Causes skin irritation.
 Causes serious eye irritation.
 Toxic if inhaled.

Precautionary statements

- Prevention** : Not applicable.
- Response** : Wear eye or face protection. Avoid breathing vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
- Storage** : Not applicable.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : None known.
- Hazards not otherwise classified** : None known.
 Not available.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Chemical name** : Mixture
- Other means of identification** : FO00016684

CAS number/other identifiers

Ingredient name	%	CAS number
Benzene, methyl-	>= 50 - <= 75	108-88-3

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 3 of 20
 Print Date 07/03/2021

n-Butyl acetate	>= 10 - <= 25	123-86-4
Isopropanol	>= 10 - < 20	67-63-0
2-Butoxy ethanol	>= 5 - <= 10	111-76-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as

SAFETY DATA SHEET**SOLV1540 SCREEN SOLV/LACQ. THINNER**

Version Number 1.1
Revision Date 07/02/2021

Page 4 of 20
Print Date 07/03/2021

a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed**Potential acute health effects**

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Toxic if inhaled.
- Skin contact** : Causes skin irritation.
- Ingestion** : Harmful if swallowed.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures
--

Extinguishing media

- Suitable extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical or CO₂.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.

SAFETY DATA SHEET**SOLV1540 SCREEN SOLV/LACQ. THINNER**

Version Number 1.1
Revision Date 07/02/2021

Page 5 of 20
Print Date 07/03/2021

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 6 of 20
 Print Date 07/03/2021

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Benzene, methyl-	OSHA PEL 1989 (1989-03-01) TWA 375 mg/m3 100 ppm STEL 560 mg/m3 150 ppm OSHA PEL Z2 (1993-06-30) TWA 200 ppm CEIL 300 ppm AMP 500 ppm NIOSH REL (1994-06-01)

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 7 of 20
 Print Date 07/03/2021

	<p>TWA 375 mg/m³ 100 ppm STEL 560 mg/m³ 150 ppm ACGIH TLV (2006-11-17) TWA 20 ppm</p>
n-Butyl acetate	<p>OSHA PEL 1989 (1989-03-01) TWA 710 mg/m³ 150 ppm STEL 950 mg/m³ 200 ppm OSHA PEL (1993-06-30) TWA 710 mg/m³ 150 ppm NIOSH REL (1994-06-01) TWA 710 mg/m³ 150 ppm STEL 950 mg/m³ 200 ppm ACGIH TLV (2016-03-01) STEL 150 ppm TWA 50 ppm</p>
Isopropanol	<p>OSHA PEL 1989 (1989-03-01) TWA 980 mg/m³ 400 ppm STEL 1,225 mg/m³ 500 ppm OSHA PEL (1993-06-30) TWA 980 mg/m³ 400 ppm NIOSH REL (1994-06-01) TWA 980 mg/m³ 400 ppm STEL 1,225 mg/m³ 500 ppm ACGIH TLV (2003-01-01) TWA 200 ppm STEL 400 ppm</p>
2-Butoxy ethanol	<p>ACGIH TLV (2003-01-01) TWA 20 ppm NIOSH REL (1994-06-01) Absorbed through skin. TWA 24 mg/m³ 5 ppm OSHA PEL 1989 (1989-03-01) Absorbed through skin. TWA 120 mg/m³ 25 ppm OSHA PEL (1993-06-30) Absorbed through skin. TWA 240 mg/m³ 50 ppm</p>

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

SAFETY DATA SHEET**SOLV1540 SCREEN SOLV/LACQ. THINNER**

Version Number 1.1
Revision Date 07/02/2021

Page 8 of 20
Print Date 07/03/2021

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties**Appearance**

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
Revision Date 07/02/2021

Page 9 of 20
Print Date 07/03/2021

Physical state	: liquid [liquid]
Color	: NOT APPLICABLE
Odor	: Not available.
Odor threshold	: Not available.
pH	: Not available.
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Not available.
Burning time	: Not available.
Burning rate	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: Not available. Upper: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: Not available.
Solubility	: Not available.
Solubility in water	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
SADT	: Not available.
Viscosity	: Dynamic: Not available. Kinematic: Not available.

Aerosol product

Heat of combustion	: Not available.
Ignition distance	: Not available.
Enclosed space ignition - Time equivalent	: Not available.
Enclosed space ignition - Deflagration density	: Not available.
Flame height	: Not available.
Flame duration	: Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 10 of 20
 Print Date 07/03/2021

- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Keep away from extreme heat and oxidizing agents.
- Incompatible materials** : Keep away from strong acids.
Oxidizer.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Benzene, methyl-				
	LD50 Oral	Rat	636 mg/kg	-
	LC50 Inhalation Vapor	Rat	49 Mg/l	4 h
Acetic acid, butyl ester				
	LD50 Oral	Rat	10,768 mg/kg	-
	LC50 Inhalation Gas.	Rat	390 ppm	4 h
	LD50 Dermal	Rabbit	17,600 mg/kg	-
2-Propanol				
	LD50 Oral	Rat	5,000 mg/kg	-
	LD50 Dermal	Rabbit	12,800 mg/kg	-
Ethanol, 2-butoxy-				
	LD50 Oral	Rat	250 mg/kg	-
	LC50 Inhalation Gas.	Rat	450 ppm	4 h
	LD50 Dermal	Rabbit	220 mg/kg	-

Conclusion/Summary : Mixture. Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Benzene, methyl-	Skin - Mild irritant	Pig	-	24 hrs	-
	Skin - Mild irritant	Rabbit	-		-
	Skin - Moderate irritant	Rabbit	-		-
	Skin - Moderate irritant	Rabbit	-	24 hrs	-
	Eyes - Mild irritant	Rabbit	-		-
	Eyes - Severe irritant	Rabbit	-	24 hrs	-

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 11 of 20
 Print Date 07/03/2021

	Eyes - Mild irritant	Rabbit	-	0.008 hrs	-
Acetic acid, butyl ester	Eyes - Moderate irritant	Rabbit	-		-
	Skin - Moderate irritant	Rabbit	-	24 hrs	-
2-Propanol	Eyes - Moderate irritant	Rabbit	-	24 hrs	-
	Skin - Mild irritant	Rabbit	-		-
	Eyes - Severe irritant	Rabbit	-		-
	Eyes - Moderate irritant	Rabbit	-		-
Ethanol, 2-butoxy-	Eyes - Moderate irritant	Rabbit	-	24 hrs	-
	Eyes - Severe irritant	Rabbit	-		-
	Skin - Mild irritant	Rabbit	-		-

Conclusion/Summary

Skin : Mixture.Not fully tested.
Eyes : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Benzene, methyl-	-	3	-
Ethanol, 2-butoxy-	-	3	-

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 12 of 20
 Print Date 07/03/2021

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
2-Propanol	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Toxic if inhaled.
- Skin contact** : Causes skin irritation.
- Ingestion** : Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following: pain or irritation, watering, redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following: irritation, redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 13 of 20
 Print Date 07/03/2021

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
SOLV1540 SCREEN SOLV/LACQ. THINNER	874.6 mg/kg	4,400 mg/kg	2,017.2 ppm	N/A	N/A
Benzene, methyl-	636 mg/kg	N/A	N/A	49 Mg/l	N/A
Acetic acid, butyl ester	10,768 mg/kg	17,600 mg/kg	390 ppm	N/A	N/A
2-Propanol	5,000 mg/kg	12,800 mg/kg	N/A	N/A	N/A
Ethanol, 2-butoxy-	250 mg/kg	220 mg/kg	450 ppm	N/A	N/A

- Other information** : This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Benzene, methyl-	Acute LC50 5.5 Mg/l Fresh water	Fish - Oncorhynchus kisutch	96 h
	Acute EC50 11.6 Mg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus	48 h
	Acute EC50 6 Mg/l Fresh water	Daphnia - Daphnia magna	48 h

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 14 of 20
 Print Date 07/03/2021

	Acute EC50 0.0125 Mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 h
	Chronic NOEC 1 Mg/l Fresh water	Daphnia - Daphnia magna	21 d
Acetic acid, butyl ester			
	Acute LC50 18 Mg/l Fresh water	Fish - Pimephales promelas	96 h
	Acute LC50 32 Mg/l Marine water	Crustaceans - Artemia salina	48 h
2-Propanol			
	Acute LC50 6.55 Mg/l Fresh water	Fish - Pimephales promelas	96 h
	Acute EC50 7,550 Mg/l Fresh water	Daphnia - Daphnia magna	48 h
	Acute LC50 1,400 Mg/l Marine water	Crustaceans - Crangon crangon	48 h
Ethanol, 2-butoxy-			
	Acute LC50 1,250 Mg/l Marine water	Fish - Menidia beryllina	96 h
	Acute EC50 > 1,000 Mg/l Fresh water	Daphnia - Daphnia magna	48 h
	Acute LC50 800 Mg/l Marine water	Crustaceans - Crangon crangon	48 h

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Benzene, methyl-	2.73	90.00	low
Acetic acid, butyl ester	2.3	-	low
2-Propanol	0.05	-	low
Ethanol, 2-butoxy-	0.81	-	low

Mobility in soil

Soil/water partition coefficient (KOC) : Not available.

Other adverse effects : No known significant effects or critical hazards.

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 15 of 20
 Print Date 07/03/2021

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Listed

Ingredient	CAS #	Status	Reference number
Benzene, methyl-	108-88-3	Listed	
Ethyl acetate	141-78-6	Listed	

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA : Consult mode specific transport rules

International Water IMO/IMDG : Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations : **United States - TSCA 12(b) - Chemical export notification:** None of the components are listed.

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 16 of 20
 Print Date 07/03/2021

United States - TSCA 4(a) - Final Test Rules: Not listed
United States - TSCA 4(a) - ITC Priority list: Not listed
United States - TSCA 4(a) - Proposed test rules: Not listed
United States - TSCA 4(f) - Priority risk review: Not listed
United States - TSCA 5(a)2 - Final significant new use rules: Not listed
United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed
United States - TSCA 5(e) - Substances consent order: Not listed
United States - TSCA 6 - Final risk management: Not listed
United States - TSCA 6 - Proposed risk management: Not listed
United States - TSCA 8(a) - Chemical risk rules: Not listed
United States - TSCA 8(a) - Dioxin/Furane precursor: Not listed
United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed
United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
United States - TSCA 8(d) - Health and safety studies: Not listed
United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Benzene, methyl-

United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed
United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed
United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed
United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Listed
Clean Air Act Section 602 Class I Substances : Not listed
Clean Air Act Section 602 Class II Substances : Not listed
DEA List I Chemicals (Precursor Chemicals) : Not listed
DEA List II Chemicals (Essential Chemicals) : Listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
---------------	---------	------------------

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 17 of 20
 Print Date 07/03/2021

Benzene, methyl-	108-88-3	1,000 lb(s) 454 kg 454 kg 1,000 lb(s)
n-Butyl acetate	123-86-4	5,000 lb(s) 2,270 kg

SARA 311/312

Classification : ACUTE TOXICITY - oral - Category 4
 ACUTE TOXICITY - inhalation - Category 3
 SKIN IRRITATION - Category 2
 EYE IRRITATION - Category 2A

Composition/information on ingredients

Name	%	Classification
Benzene, methyl-	>= 50 - <= 75	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY - oral - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
Acetic acid, butyl ester	>= 10 - <= 25	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - inhalation - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
2-Propanol	>= 10 - < 20	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Narcotic effects - Category 3
Ethanol, 2-butoxy-	>= 5 - <= 10	FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY - oral - Category 3 ACUTE TOXICITY - dermal - Category 3 ACUTE TOXICITY - inhalation - Category 2 EYE IRRITATION - Category 2A

Form R - Reporting requirements

Product name	CAS number	%
--------------	------------	---

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 18 of 20
 Print Date 07/03/2021

Benzene, methyl-	108-88-3	>= 50 - <= 75
2-Butoxy ethanol	111-76-2	>= 5 - <= 10

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Not applicable.

State regulations

- Massachusetts** : None of the components are listed.
- New York** : The following components are listed:
 Benzene, methyl-
 n-Butyl acetate
 Ethyl acetate
- New Jersey** : The following components are listed:
 Benzene, methyl-
 n-Butyl acetate
 Isopropanol
 Ethyl acetate
 2-Butoxy ethanol
- Pennsylvania** : The following components are listed:
 Benzene, methyl-

 n-Butyl acetate

 Isopropanol

 Ethyl acetate

 2-Butoxy ethanol

California Prop. 65

 **WARNING:** This product can expose you to Benzene, methyl-, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Benzene, methyl-	-	Yes.

United States inventory (TSCA 8b) : All components are active or exempted.

Canada inventory : All components are listed or exempted.

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
 Revision Date 07/02/2021

Page 19 of 20
 Print Date 07/03/2021

International regulations

Inventory list

- Australia : All components are listed or exempted.
- Canada : All components are listed or exempted.
- China : All components are listed or exempted.
- Europe inventory : All components are listed or exempted.
- Japan : All components are listed or exempted.
- New Zealand : All components are listed or exempted.
- Philippines : All components are listed or exempted.
- Republic of Korea : All components are listed or exempted.
- Taiwan : All components are listed or exempted.
- Turkey : All components are listed or exempted.
- United States : All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

- Date of printing : 07/03/2021
- Date of issue/Date of revision : 07/02/2021
- Date of previous issue : 07/02/2021
- Version : 1.1

Key to abbreviations

- : ATE = Acute Toxicity Estimate
- : BCF = Bioconcentration Factor
- : GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- : IATA = International Air Transport Association
- : IBC = Intermediate Bulk Container
- : IMDG = International Maritime Dangerous Goods
- : LogPow = logarithm of the octanol/water partition coefficient
- : MARPOL = International Convention for the Prevention of Pollution From

SAFETY DATA SHEET

SOLV1540 SCREEN SOLV/LACQ. THINNER

Version Number 1.1
Revision Date 07/02/2021

Page 20 of 20
Print Date 07/03/2021

Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References

: Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.